CONLOX®

Made in Germany

LANIOL

LNO-SYE06B-06F

CONLOX® Socket 6 short
incl. 6A Sicherung, Federzugklemme
with 6A fuse, spring terminal







Technische Daten / Technical Data			
Anschlusstyp Connection type	Innensechskant 6 [mm] Hexagon socket 6 [mm]	Nennspannung Nominal voltage	U_0 / U 300 / 500 [VAC] U_0 / U 250 / 250 [VDC]
Befestigung / Drehmoment Fastening / torque	TX10 / 1,2 [Nm]	Bemessungsstrom Rated current	6,0 [A]
Anschlussarten Conductor types	starr, flexibel, Endhülsen solid, flexible, ferrules	Abisolierlänge Stripping length	6 … 8 [mm]
Federzugklemme Spring terminal	0,75 … 2,5 [mm²] 20 … 14 [AWG]	Schutzart Ingress protection	IP 20
Produktnorm Product norm	DIN EN IEC 60999 DIN EN IEC 61984 DIN EN IEC 62444	Kabelbindergröße Cable tie size	2,4 [mm] 0,1 [in]
Betriebstemperatur Operating temperature	-25 … +85 [°C] -13 … +185 [°F]	Größe Size	43 x 31 x 15 [mm] 1,69 x 1,22 x 0,59 [in]
Lager- / Montagetemperatur Storage- / mount temperature	-25 … +55 [°C] -13 … +131 [°F]	Gewicht Weight	9 [g] 0,02 [lb]
Ausschaltvermögen Sicherung Fuse rated breaking capacity	70kA [VAC] 10kA [VDC]	Gehäusefarbe Housing colour	Gelb Yellow

Montage mit dem PlugSafe Tool
Mounting with the PlugSafe tool



Die CONLOX® Socket 6 short ermöglicht eine elektrische Verbindung an besonders kurzen Schrauben mit 6mm Innensechskant wie sie in V- bzw. Rahmenklemmen zu finden* sind. Damit werden Verbindungen zu passendem Equipment über starre, flexible oder Anschlussleitungen mit Aderendhülsen realisiert. CONLOX® können von geschulten Elektrofachkräften unter Spannung montiert werden.

The CONLOX® Socket short 6 enables an connection to special short 6mm hexagon sockets which can be found* in V-clamps or frame clamps. Connections to suitable equipment via solid, stranded or cables with ferrules can be realized. CONLOX® can be mounted by electrically qualified personnel under voltage.

* Die Socket Länge muss der Einbausituation entsprechen.
* Die Socket length must correspond to the installation situation.

Artikel-Nr. / Article-no.:	
St. / pcs.	GTIN
1	4260728984037
200	4260728984044
2.000	4260728984051

ZolltarifNr.: 85369010

Rev. 1.23 – 04 / 2023