CONLOX®

Made in Germany

LANIOL

# LNO-SBU06B-00F

## CONLOX® Socket 6 short N
ohne Sicherung, Federzugklemme
without fuse, spring terminal





| Technische Daten / Technical Data | | | |
|---|---|---|---|
| Anschlusstyp<br>Connection type | Innensechskant 6 [mm]<br>Hexagon socket 6 [mm] | Nennspannung<br>Nominal voltage | $U_0$ / U 300 / 500 [VAC]<br>$U_0$ / U 250 / 250 [VDC] |
| Befestigung / Drehmoment<br>Fastening / torque | TX10 / 1,2 [Nm] | Bemessungsstrom<br>Rated current | 6,0 [A] |
| Anschlussarten<br>Conductor types | starr, flexibel, Endhülsen<br>solid, flexible, ferrules | Abisolierlänge<br>Stripping length | 6 … 8 [mm] |
| Federzugklemme<br>Spring terminal | 0,75 … 2,5 [mm²]<br>20 … 14 [AWG] | Schutzart<br>Ingress protection | IP 20 |
| Produktnorm<br>Product norm | DIN EN IEC 60999<br>DIN EN IEC 61984<br>DIN EN IEC 62444 | Kabelbindergröße<br>Cable tie size | 2,4 [mm]<br>0,1 [in] |
| Betriebstemperatur<br>Operating temperature | -25 … +85 [°C]<br>-13 … +185 [°F] | Größe<br>Size | 43 x 31 x 15 [mm]<br>1,69 x 1,22 x 0,59 [in] |
| Lager- / Montagetemperatur<br>Storage- / mount temperature | -25 … +55 [°C]<br>-13 … +131 [°F] | Gewicht<br>Weight | 7 [g]<br>0,02 [lb] |
| | | Gehäusefarbe<br>Housing colour | Blau<br>Blue |

## Montage mit dem PlugSafe Tool
Mounting with the PlugSafe tool



Die CONLOX® Socket 6 N short ermöglicht eine elektrische Verbindung an besonders kurzen Schrauben mit 6mm Innensechskant wie sie in V- bzw. Rahmenklemmen zu finden sind. Damit werden Verbindungen zu passendem Equipment über starre, flexible oder Anschlussleitungen mit Aderendhülsen realisiert. CONLOX® können von geschulten Elektrofachkräften unter Spannung montiert werden.

The CONLOX® Socket short 6 N enables an connection to special short 6mm hexagon sockets which can be found in V-clamps or frame clamps. Connections to suitable equipment via solid, stranded or cables with ferrules can be realized. CONLOX® can be mounted by electrically qualified personnel under voltage.

| Artikel-Nr. / Article-no.: | |
|---|---|
| St. / pcs. | GTIN |
| 1 | 4260728984532 |
| 200 | 4260728984549 |
| 2.000 | 4260728984556 |
| | |

ZolltarifNr.: 85369010

* Die Socket Länge muss der Einbausituation entsprechen.
* Die Socket length must correspond to the installation situation.

Rev. 1.23 – 04 / 2023